DuraVar Conversion Varnish

DuraVar Conversion Varnish is a clear, non-yellowing wood stock coating. DuraVar is highly resistant to lubricants, bore solvents, water, impact and abrasion. DuraVar is a two part catalyzed coating which works both as a sanding wood sealer and a top coat.

DuraVar can ONLY be applied as a SPRAY!

Application Instructions:

1. Sand wood surface smooth
2. Use a tack cloth to remove all sanding dust
3. Stain wood and allow to dry thoroughly
4. Spray a smooth even coat of DuraVar
5. Allow to dry 24 hours
6. Sand with 220 grit
7. Spray a second coat of DuraVar
8. Allow to dry 24 hours before putting the firearm to use
9. A 3rd or 4th coat can be applied for a rich, deep finish. Sand between each coat.

Catalyzing Instructions:

1. Mix 4oz of DuraVar to 1oz of DuraVar Catalyst or 2oz DuraVar to 1/2oz Catalyst
2. Allow 30 minutes before using
3. DuraVar has an 8 hour working life
4. Discard any DuraVar remaining after 8 hours. Do not return to the original container.

Always wear protective gloves, eyewear, and an approved respirator. Be in a well-ventilated area. Read all warnings and first aid information, and read and follow all instructions when using any DuraCoat® products.

Lauer Custom Weaponry
3601 129th St. Chippewa Falls, WI 54729
1-800-830-6677
www.lauerweaponry.com