US Patent #s 7,412,918 and 7,682,661

Peel ‘N Spray™ Templates

Please note: These instructions are meant as a guide for use with DuraCoat® finishes. We cannot guarantee results or behavior when used with other coatings.

Our Peel ‘N Spray™ templates will save you the time and frustration of developing your own masking. The scale and shape of our peel and spray templates will give you professional, repeatable results time after time.

Peel ‘N Spray™ templates are easy to use, just peel and stick. Spray over the covered and uncovered areas. When you remove the templates, some adhesive residue may be left behind. This residue needs to be removed before you continue. Do not spray clear or additional colors over the residue. This residue can be easily removed with a soft cloth and our Template Adhesive Remover and can be done as soon as the latest color is dry to the touch. (Do NOT use other solvents).

You can minimize the amount of residue left behind by allowing time between colors. Wait until preceding color is dry. If you are using an oven to speed up production allow parts to cool to room temperature before applying the next layer of templates. A little patience and organization will give you the best results.

Peel ‘N Spray™ Templates need to be stored in a cool, dark, and dry place. Exposure to heat, moisture, or sunlight will shorten the shelf life and may damage the adhesive. The shelf life of Peel ‘N Spray™ Templates is approximately one year when stored in proper conditions. After one year, you may notice a decrease in the effectiveness of the adhesive.

DISCLAIMER: Peel ‘N Spray™ Templates go through a quality control check but it is still possible that there may be variances in the depth of cut. It is possible that some areas are cut deeper than necessary and other areas may be cut too shallow requiring you to use a knife to free the piece from the surrounding shapes.

Manufactured By: DuraCoat Finishes, LLC
601 S. Broadway Blvd.
Salina, KS 67401
715-720-6128